

SECTION

RSU

REAR SUSPENSION

A

B

C

CONTENTS

RSU

PRECAUTIONS	2	LEAF SPRING	7	F
Precautions	2	Removal and Installation	7	
NOISE, VIBRATION AND HARSHNESS (NVH)		REMOVAL	8	
TROUBLESHOOTING	3	INSPECTION AFTER REMOVAL	9	G
NVH Troubleshooting Chart	3	INSTALLATION	9	
REAR SUSPENSION ASSEMBLY	4	SERVICE DATA AND SPECIFICATIONS (SDS)	11	
Components	4	General Specifications (Rear)	11	H
On-Vehicle Inspection and Service	5	Wheelarch Height (Unladen*1)	11	
SHOCK ABSORBER	6			
Removal and Installation	6			I
REMOVAL	6			
INSPECTION AFTER REMOVAL	6			J
INSTALLATION	6			

PRECAUTIONS

PRECAUTIONS

PFP:00001

Precautions

EES002JD

- When installing rubber parts, final tightening must be carried out under unladen condition* with tires on ground.
 - * Fuel, radiator coolant, and engine oil are full. Spare tire, jack, hand tools, and mats are in their designated positions. Oil will shorten the life of rubber bushings, so wipe off any spilled oil immediately.
- Lock nuts are not reusable. Always use new lock nuts for installation. New lock nuts are pre-oiled, do not apply any additional lubrication.

NOISE, VIBRATION AND HARSHNESS (NVH) TROUBLESHOOTING

NOISE, VIBRATION AND HARSHNESS (NVH) TROUBLESHOOTING

PFP:54000

NVH Troubleshooting Chart

EES002JF

Use the chart below to help you find the cause of the symptom. If necessary, repair or replace the parts.

Reference page		RSU-4	RSU-6	RSU-4	RSU-4	RSU-9	RSU-4	PR-2, "NVH Troubleshooting Chart"	RFD-7 (with LSD), RFD-39 (with LD)	RAX-5, "NVH Troubleshooting Chart"	WT-2, "NVH Troubleshooting Chart"	WT-2, "NVH Troubleshooting Chart"	BR-5, "NVH Troubleshooting Chart"	PS-5, "NVH Troubleshooting Chart"
Possible cause and SUSPECTED PARTS		Improper installation, looseness	Shock absorber deformation, damage or deflection	Bushing or mounting deterioration	Parts interference	Spring fatigue	Suspension looseness	PROPELLER SHAFT	REAR FINAL DRIVE	AXLE	TIRES	ROAD WHEEL	BRAKES	STEERING
Symptoms	Noise	x	x	x	x	x	x	x	x	x	x	x	x	x
	Shake	x	x	x	x		x	x		x	x	x	x	x
	Vibration	x	x	x	x	x		x		x	x			x
	Shimmy	x	x	x	x					x	x	x	x	x
	Shudder	x	x	x						x	x	x	x	x
	Poor quality ride or handling	x	x	x	x	x	x			x	x	x		

x: Applicable

A
B
C
D
E
F
G
H
I
J
K
L
M

RSU

REAR SUSPENSION ASSEMBLY


REAR SUSPENSION ASSEMBLY

PFP:55020

Components

EES002JG

SEC. 431



MEIB9017E

- | | | |
|---------------------|-------------------------------|--------------------------------|
| 1. Rear final drive | 2. Rear leaf spring | 3. Rear spring bushing (front) |
| 4. Rear spring pad | 5. Rear spring bushing (rear) | 6. Rear spring shackle |
| 7. Bumper | 8. Rear spring clip U-bolts | 9. Rear spring shackle bushing |

REAR SUSPENSION ASSEMBLY

10. Shock absorber

11. Bumper

12. Shock absorber (left side)

13. Shock absorber (right side)

14. Damper


CAUTION:

When installing the components with rubber bushings, the final tightening of the nuts and bolts must be done with the vehicle in an unladen condition (the fuel, engine coolant, and engine oil full; the spare tire, jack, hand tools and mats in their designated positions) with the tires on the ground.

On-Vehicle Inspection and Service

EES002JH


- Check the rear suspension parts for any excessive play, cracks, wear, and other damage.
- Shake each rear wheel to check for any excessive play as shown.




- Tighten all of the nuts and bolts to the specified torque.

CAUTION:

When installing the components with rubber bushings, the final tightening of the nuts and bolts must be done with the vehicle in an unladen condition (the fuel, engine coolant, and engine oil full; the spare tire, jack, hand tools and mats in their designated positions) with the tires on the ground.



- Check the shock absorbers for oil leaks, deformation, and other damage.
- Check the shock absorber bushings for excessive wear and other damage.



SHOCK ABSORBER

SHOCK ABSORBER


PFP:56210

Removal and Installation

EES002JI

REMOVAL

1. Support the rear final drive and suspension assembly using a suitable jack.
2. Remove the shock absorber upper and lower nuts and bolts.



3. Remove the shock absorber.

INSPECTION AFTER REMOVAL

- Inspect the shock absorber for any oil leaks, cracks, or deformations. Replace the shock absorber as necessary.
- Check the shock absorber for smooth operation through a full stroke, both compression and extension.
- If rubber bushings are cracked or deformed, replace rubber bushings.

INSTALLATION

Installation is in the reverse order of removal.

Shock absorber upper and lower nuts : Refer to [RSU-4, "Components"](#) .

LEAF SPRING


LEAF SPRING

Removal and Installation

PFP:55020

EES002JJ

SEC. 431



: N·m (kg-m, ft-lb)

: Always replace after every disassembly.

- | | | |
|---------------------|-------------------------------|--------------------------------|
| 1. Rear final drive | 2. Rear leaf spring | 3. Rear spring bushing (front) |
| 4. Rear spring pad | 5. Rear spring bushing (rear) | 6. Rear spring shackle |
| 7. Bumper | 8. Rear spring clip U-bolts | 9. Rear spring shackle bushing |

LEAF SPRING


- | | | |
|---------------------------------|------------|--------------------------------|
| 10. Shock absorber | 11. Bumper | 12. Shock absorber (left side) |
| 13. Shock absorber (right side) | 14. Damper | |

CAUTION:


When installing the components with rubber bushings, the final tightening of the nuts and bolts must be done with the vehicle in an unladen condition (the fuel, engine coolant, and engine oil full; the spare tire, jack, hand tools and mats in their designated positions) with the tires on the ground.

REMOVAL


1. Support the rear final drive assembly with a suitable jack to relieve the tension from the rear leaf spring.
 - The axle weight should be supported, but there should be no compression in the rear leaf spring.
2. Remove the shock absorber lower nut and bolt.




3. Remove the four rear spring clip U-bolt nuts, then remove the rear spring pad.



4. Remove the rear spring shackle and bushings.



5. Remove the rear leaf spring front nut and bolt.
6. Remove the rear leaf spring.





LEAF SPRING

INSPECTION AFTER REMOVAL


- Check the rear leaf spring for any cracks or damage. Replace the rear leaf spring if necessary.
- Check the rear spring shackle, rear spring clip U-bolts, bumper, and rear spring pad for excessive wear, cracks, straightness, and damage. Replace any components if necessary.
- Check all bushings for deformation and cracks. Replace any bushings if necessary.

INSTALLATION


1. Apply soapsuds to all of the rubber bushings.
2. Install the rear spring shackle and rear leaf spring front nut and bolt. Finger-tighten the nuts.
3. Install the rear spring clip U-bolts and bumper on top of the rear leaf spring.
4. Install the rear spring pad, and nuts under the axle case.
5. Tighten diagonally and in few steps the rear spring clip U-bolt nuts, until the lengths of all the exposed rear spring clip U-bolt threads under spring pad are equal in length, within a tolerance of 3 mm (0.12 in).
Tighten nuts to specification. Refer to [RSU-4, "Components"](#).



6. Install the shock absorber, and finger-tighten the nuts.




7. Remove the jack supporting the rear final drive assembly and bounce the rear of the vehicle to stabilize the suspension.



LEAF SPRING

8. Tighten the rear spring shackle nuts, rear leaf spring front nut, and shock absorber nuts to specification.
- When installing the components with rubber bushings, the final nut tightening must be carried out under unladen* conditions with the tires on level ground.
- * (Fuel, radiator coolant and engine oil full. Spare tire, jack, hand tools and mats in designated positions.)



SERVICE DATA AND SPECIFICATIONS (SDS)

SERVICE DATA AND SPECIFICATIONS (SDS)

PFP:00030

General Specifications (Rear)

EES002JK


Suspension type	Rigid axle with semi-elliptic leaf springs
Shock absorber type	Double-acting hydraulic

Wheelarch Height (Unladen*¹)

EES002JL

King Cab

Unit: mm (in)




LEIA0085E

Engine type	YD25				
Drive type	2WD		4WD		
Applied model	XE		XE	XE, SE	SE
Tire size	235/70R16	255/70R16	235/70R16	255/70R16	255/65R17
Front wheelarch height (Hf)	833 - 863 (32.80 - 33.98)	845 - 875 (33.27 - 34.45)	846 - 876 (33.31 - 34.49)	858 - 888 (33.78 - 34.96)	861 - 891 (33.90 - 35.08)
Rear wheelarch height (Hr)	874 - 904 (34.41 - 35.59)	877 - 907 (34.53 - 35.71)	878 - 908 (34.57 - 35.75)	891 - 921 (35.08 - 36.26)	893 - 923 (35.16 - 36.34)

*1: Fuel, radiator coolant and engine oil full. Spare tire, jack, hand tools and mats in designated positions.

Double Cab

Unit: mm (in)



LEIA0085E

Engine type	YD25				
Drive type	2WD		4WD		
Applied model	SE		XE	XE, SE	SE
Tire size	235/70R16	255/70R16	235/70R16	255/70R16	255/65R17
Front wheelarch height (Hf)	832 - 862 (32.76 - 33.94)	844 - 874 (33.23 - 34.41)	846 - 876 (33.31 - 34.49)	857 - 887 (33.74 - 34.92)	860 - 890 (33.86 - 35.04)
Rear wheelarch height (Hr)	872 - 902 (34.33 - 35.51)	885 - 915 (34.84 - 36.02)	877 - 907 (34.53 - 35.71)	889 - 919 (35.00 - 36.18)	891 - 921 (35.08 - 36.26)

*1: Fuel, radiator coolant and engine oil full. Spare tire, jack, hand tools and mats in designated positions.

SERVICE DATA AND SPECIFICATIONS (SDS)
